



LumiLast™ LED MR16: Redefining Energy Efficient



BENEFITS INCLUDE
 Unrivaled Reduction in Energy Consumption™
 No projected UV rays
 No projected heat
 Flexible viewing angles 15, 30, 45, 60 degrees
 Wide color spectrum available
 Simple retrofit installation
 3 Watts 12 Volts
 No Mercury
 Recyclable



LumiLast™ MR 16 LED

Data

Note

	Data	Note
TRIM STYLES	Black, Stainless, Brass	
VIEWING (BEAM ANGLE)	15,30, 45, 60 degrees	30 degrees for this project
HOUSING	Pure Aluminum	recyclable
BASE OUTER DIMENSIONS	50mm × 47.5mm	
BASE TYPE	GX5.3 Compatible	plugs in same fixture
WEIGHT	55 Grams	
POWER REQUIREMENTS	12V AC(50~60Hz) / 12V DC	
WATTS	3 watts	
TRANSFORMER SPEC	Low-Voltage Magnetic or Electronic to provide 12V AC	
OPERATING TEMP.	20 ~ 40°C	
COLORS	Incandescent Warm 2700k, Warm 3200k, Day-light white 4000k, cool white 5000k, B, G, R, A	3200k for this project
ILLUMINANCE	240-360 directional lumens	no wasted light in can
CRI	>82	
WARRANTY	3 years @ 24 hrs a day or 24000 hrs	