



LumiLast™ Photoluminescent Exit Signs: Redefining Energy Efficient



- BENEFITS INCLUDE**
- No power required 0 watts
 - 25 year solution
 - UL Listed
 - Aesthetic Appeal
 - Fully Recycleable
 - Simple clean installation
 - Aluminum Based
 - Polycarbonate face for Durability
 - Non Toxic



LumiLast™

Photoluminescent Exit Signs

Data

Note

	Data	Note
TRIM STYLES	Black, Aluminum	
VIEWINGDISTANCE	75 ft	
HOUSING	Pure Aluminum	Recyclable
APPROVED COLORS	Black , Green, Red	
WEIGHT	1 lb	
POWER REQUIREMENTS	None	
WATTS	Zero watts	Cap wires for good!
LIGHT REQUIRED FOR PROPER OPERATION	5 ft candles at face of sign	
COMPLIANCE	UL-924 UL Exit Signs DIN 67510-1, ISO/CD 15370, ASTM 162, ASTM 662, ASTM E 2072-00, NFPA Life Safety Code 101	Dont be fooled by immitation signs
APPROVALS	Energy Star for United States UL-924 US and Canada State of California State Fire Marshall Listing	
AFTERGLOW LUMI-NANCE	mcd/m2 = 52@90 minutes	